

ZPMV2.E210623 - Wiring, Printed - Component

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

CIRCUIT SYSTEMS (INDIA) LTD

B-24 Gidc Electronics Estate

Sector 25

Gandhinagar, Gj 382044 INDIA

E210623

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Solder Limits C	sec	Max	Meets UL796 Class	C	I
	Min mm(in)	Min Edge mm(in)			Area Diam mm(in)			Oper Temp C			
Mass laminated (multilayered) printed wiring boards.											
B-	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	274	10	105	-	All	-
B-0	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	274	10	105	V-0	All	-
B-1	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	274	10	105	V-1	-	-
Multilayer-printed wiring boards.											
1-	0.13 (0.005)	0.13 (0.005)	17 (0.67) Int:102	DS	101.6 (4.0)	274	10	105	-	All	-
1-0	0.13 (0.005)	0.13 (0.005)	17 (0.67) Int:102	DS	101.6 (4.0)	274	10	105	V-0	All	-
1-1-	0.13 (0.005)	0.13 (0.005)	17 (0.67) Int:102	DS	101.6 (4.0)	274	10	105	V-1	All	-
2-	0.13 (0.005)	0.13 (0.005)	17 (0.67) Int:102	DS	101.6 (4.0)	285	10	105	-	All	-
2-0	0.13 (0.005)	0.13 (0.005)	17 (0.67) Int:102	DS	101.6 (4.0)	285	10	105	V-0	All	-
2-1	0.13 (0.005)	0.13 (0.005)	17 (0.67) Int:102	DS	101.6 (4.0)	285	10	105	V-1	All	-
3-0	0.13 (0.005)	0.38 (0.015)	17 (0.67) Int:107	DS	101.6 (4.0)	288	10	120	V-0	All	-
4-0	0.13 (0.005)	0.38 (0.015)	17 (0.67) Int:107	DS	50.8 (2.0)	288	10	130	V-0	All	-
6-0\$	0.13 (0.005)	0.38 (0.015)	17 (0.67) Int:107	DS	254 (10.0)	288	10	120	V-0	All	-
B-2	0.20 (0.008)	0.61 (0.024)	17 (0.67) Int:70	DS	25.4 (1.0)	275	10	105	V-0	-	-
M	0.13 (0.005)	0.38 (0.015)	18 (0.71) Int:103	DS	38.1 (1.5)	274	10	105	-	-	-
M0	0.13 (0.005)	0.38 (0.015)	18 (0.71) Int:103	DS	38.1 (1.5)	274	10	105	V-0	-	-
Single layer printed wiring boards.											

-0	0.15 (0.006)	0.46 (0.018)	17 (0.67)	DS	19.1 (0.8)	274	12	105	V-0	▲	-
-3	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	260	10	105	V-0	▲	-
1	0.13 (0.005)	0.13 (0.005)	17 (0.67)	DS	101.6 (4.0)	274	10	105	V-0	All	-
2	0.13 (0.005)	0.13 (0.005)	17 (0.67)	DS	101.6 (4.0)	274	10	105	V-0	All	-
7	0.38 (0.015)	1.14 (0.045)	17 (0.67)	DS	101.6 (4.0)	274	10	130	V-0	▲	-
8	0.13 (0.005)	0.15 (0.006)	17 (0.67)	DS	101.6 (4.0)	288	10	130	V-0	▲	-
a	0.13 (0.005)	0.13 (0.005)	17 (0.67)	DS	254 (10.0)	274	10	130	-	All	-
A-	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	274	10	105	-	▲	-
a-0	0.13 (0.005)	0.13 (0.005)	17 (0.67)	DS	254 (10.0)	274	10	130	V-0	All	-
A-0	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	274	10	105	V-0	▲	-
A-1	0.13 (0.005)	0.38 (0.015)	17.8 (0.70)	DS	25.4 (1.0)	274	10	105	V-1	All	-
A-2	0.2 (0.008)	0.61 (0.024)	17 (0.67)	DS	25.4 (1.0)	275	10	105	V-0	All	-

§ - Carbon Printing on unpierced copper and/or laminate is allowed to a maximum of 4 inches only.

Marking: Company name or tradename "CSIL" or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2018-01-10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"